

S5200E specifications

Version 1.2 – April 2015

MAIN FEATURES

Data encoding	<p>ISO Magnetic Stripe encoding - 3 tracks HiCo – LoCo JIS-2 Magnetic Stripe Encoding Chip Encoding - Contact, Contactless Multi SmartCard Encoding – 5 Contact, 3 Contactless</p>
Text and graphic personalization	<p>Embossing and single tipping with cartridge Front and/or Rear Indenting</p>
Card management	<p>Card Feeder capacity: 600 cards Card Stacker capacity: 600 cards (approx. 385 embossed cards) Reject Card Tray</p>
Operation	<p>On-Off switch button USB connectivity Device security features</p>
Performances, Duty Cycle	<p>Magnetic encoding, embossing, rear indenting, tipping: <ul style="list-style-type: none"> ▪ Up to 500cph <p>Max working time: <ul style="list-style-type: none"> ▪ Up to 8 hours a day </p> </p>

MODELS AND OPTIONS

Base Unit	<ul style="list-style-type: none"> ▪ 600 Card Feeder + 600 Card Stacker with Reject Card Tray ▪ Embosser 98 characters Drum ▪ Single tipping with cartridge ▪ MaticardPro production SW License
Options	<ul style="list-style-type: none"> ▪ Magnetic Stripe Encoding ▪ Single or Multi Smart Card Encoding station ▪ Embosser 114 characters Drum ▪ Front and/or Rear Infiller station

S5200E specifications

Version 1.2 – April 2015

DETAILED SPECIFICATIONS

Card specifications	ISO CR80, ISO 7810, ISO7816, ISO14443A&B Card material: PVC plastic, no paper, no metal Card thickness: 0,76mm (30 mil) +- ISO tolerances
Security features	Data Encryption Service Key for service/ maintenance
Device controlling	External PC with controlling SW (PC not included)
Connection	USB 2.0
Software	MaticardPro card production software Smart Card SDK Supported OS: Win 7 (32 & 64bits), Win 8, Win 8.1 to be confirmed
Power supply	Auto-switching internal power supply Input 100-240 Volts AC, 50-60 Hz – 500W Output 24 Volts DC Interchangeable external power cord
Size and Weight	L x W x H: 1430 x 550 x 700 mm, 56" x 22" x 28" Approx 85 kg

WARRANTY & CERTIFICATIONS

Warranty	12 months
Quality standards	EN 55022:2006, EN 55024:2010, IEC 61000-3-2:2009, IEC 61000-3-3:2008, CISPR 22:2008, CISPR 24:2010 RoHS CE approval Min/max operating temperature: 15° / 30 °C (59° / 86 °F) Humidity: 20% to 65% without condensation Min/max storage temperature: -5° / +70 °C (23° / 158 °F) Storage humidity: 20% to 70% without condensation

CONSUMABLES

Infill, tipping ribbon types	Infill: <ul style="list-style-type: none">▪ Black and White▪ 122 meters▪ Approx. 800 cards (front 35 chars), 2000 cards (rear 7 chars) Tipping: <ul style="list-style-type: none">▪ Black , Silver, Gold, White, Blue & Varnish▪ 122 meters▪ Approx. 4000 cards (3 lines emboss)
Cleaning material	Cleaning card for regular cleaning cycles (warranty observance) Swab for roller cleaning

Data subject to change without notice. All trademarks are the property of the respective owners